Form 238-7 8/90

STATE OF IDAHO DEPARTMENT OF WATER RESOURCES

USE TYPEWRITER OR BALLPOINT PEN

WELL DRILLER'S REPORT

State law requires that this report be filed with the Director, Department of Water Resources within 30 days after the completion or abandonment of the well.

								//			
1. WELL OWNER	7.	WATI	ER LEV	/EL				/ V			
Name South River Water ASSac	-40										
	Static water level feet below land surface.										
Address \$ 102 4th post Falls	Flowing?										
Drilling Permit No. 95-91-N-22	Controlled by: Valve Cap Plug										
Water Right Permit No. 95-8684	Temperature OF Quality										
Trace right 1 of the re-	Describe artesian or temperature zones below.										
2. NATURE OF WORK	8. WELL TEST DATA										
	☐ Pump ☐ Bailer										
☐ Abandoned (describe abandonment procedures such as	 	Discharge G.P.M. Pumping Leve						Hours F	umpec		
materials, plug depths, etc. in lithologic log)		Airly 80+					2010/	. 3			
	17.A.	- T	OUT_					 			
3. PROPOSED USE											
3. PROPOSED USE				-							
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal	9. LITHOLOGIC LOG										
☐ Industrial ☐ Stock ☐ Waste Disposal or Injection									Water		
Other (specify type)	1	Bore Depth Diam. From To				N		_	s No		
	10"		197	R	עלעוש	Dix			+	F	
4. METHOD DRILLED	10"	7_	19	BE	ack -	white	quart	- 12 /- 2 gpa	nx	Z	
.⊠ Rotary □ Air □ Hydraulic □ Reverse rotary	8"	19	90	BL	ich a	norto	lta c	Hard	\bot	+	
☐ Cable ☐ Dug ☐ Other	24	90	/60	61	un f	والميمية	<u>ي تار</u>	of med	+	+-	
	6"	140	305		cle-w	Ribe	quarter	timed		+	
5. WELL CONSTRUCTION 4/2 0'	8"	365	390		en_	white		led.	+-		
720	87	390	395			hiti	2017	Tout Med		+	
Casing schedule: ☒ Steel ☐ Concrete ☐ Other	<u> </u>	410	415			white	- great	Voite Sout	17		
Thickness Diameter From To	C 4	415	420	Bre	en 6	man	acto	mel	T		
.250 inches 8' inches + 1/3 feet 18% feet							<i>a</i> - t -		\perp		
inches 6" (NC inches 8 feet 430 feet 10 feet 1	Ĺ	<u> </u>	J.L	1	30	1075			4		
inches inches feet feet	<u> </u>					V/					
Was casing drive shoe used? ☐ Yes 🔞 No	 			-						+	
Was a packer or seal used? ☐ Yes ☑ No	├ ──	 			10	1001			+-	-	
Perforated? ☐ Yes ☒ No	<u> </u>	 	-	VDE	12	1991			_	-	
How perforated? ☐ Factory ☐ Knife ☐ Torch ☐ Gun									+	+ -	
Size of perforation inches by inches		· · · ·	Dens	+	-1 19/44	or Reso	urca		1		
Number From To			- i ve po	· –		J1 114, 14,	ZOI				
perforations feet feet						The same of	1 Kr		4		
				ļ. <u>-</u>	- A - C - C - C - C - C - C - C - C - C					_	
Well screen installed? ☐ Yes ☐ No	<u> </u>					PEN.	£ 102.	/			
Manufacturer's name	├	├	 	-	Char.	~	5	io.	+	+	
Type Model No	 	 			+	BL	TEN'NE	<i></i>	+ -	+	
Diameter Slot size Set from feet to feet	\vdash				1	NOF	1		7-		
Diameter Slot size Set from feet to feet	T					V	5200		1		
Gravel packed? ☐ Yes ᠖No ☐ Size of gravel						A. Lane				\perp	
Placed from feet to feet Surface seal depth 1 Material used in seal: □ Cement grout	L										
B Bentonite	 									+	
Sealing procedure used: Slurry pit Temp, surface casing		<u> </u>	}						+-	-	
Overbore to seal depth	 		\vdash	-					1	+	
Method of joining casing: 🗆 Threaded 🛮 🗹 Welded 🗆 Solvent						F .	1 1 1	Ĭ,	\top	1 1	
Weld											
☐ Cemented between strata	10.					/				1	
Describe access port	} '		rk start	ted	3-4	-91	finishe	d 3-8-8/	1	1	
	-										
6. LOCATION OF WELL	11.	DRIL	LERS	CERT	IFICA	TION	DP				
Sketch map location must agree with written location.	1	I/We	certify	that	all min	imum v	well const	truction stand	ards v	vere	
N	l						was remo				
Subdivision Name 1 20	l					. ^			-0.		
		Firm	Name /	40	Wel	L Sero	Ke MY	Firm No. <u>44</u>	8		
W X E	ł			•							
"	Address Hayden Soloto Date 3-11-91										
Lot No Block/No	Cinned by (Eigen Official)										
	Signed by (Firm Official)										
County Costenai	Signed by (Firm Official) Solve Walescer and (Operator) Solve Walescer										
Co N. E	(Operator) John Leller										
U SP v Amayo io	s.					~					